Reference No: 91692



Inspection - Crane Operation Checklist

Suspended Load_Preventing Operator Being Struck By Boom on Telehandler - Preventing Operator Being Struck By Boom on Telehandler

| Prompt | Establis | Improven | N/A | Explanation | Comments |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| Window on the boom-side of telehandlers or variable reach trucks is designated as safety-critical equipment? | | | | The window on the boom-side of telehandlers or variable reach trucks is designated as safety-critical equipment as it is designed as a guard to prevent operator access to the boom. | |
| On OTML owned machines a mesh cage is placed over side window on telehandler? | | | | On OTML owned machines a mesh cage is placed over side window on telehandler to prevent operator leaning out into the path of the boom. | |
| Any telehandler with damaged side windows is removed from service until the glass is replaced? | | | | Any telehandler with damaged side windows is removed from service until the glass is replaced. | |
| Supervisor to ensure that a mesh cage is provided over side window on OTML owned telehandler? | | | | Supervisor ensure that a mesh cage is provided over side window on OTML owned telehandler to prevent operator leaning out into the path of the boom. | |
| Supervisor to ensure that the window on the boom-side of telehandlers or variable reach trucks is designated as safety-critical equipment? | | | | Ensure the window on the boom-side of telehandlers or variable reach trucks is designated as safety-critical equipment as it is designed as a guard to prevent operator access to the boom. | |
| Supervisor removes from service any telehandler with damaged side windows until the glass is replaced? | | | | Supervisor removes from service any telehandler with damaged side windows until the glass is replaced? | |
| Supervisor verifies that any person required to operate a telehandler is trained and assessed competent in conduct of those operations? | | | | Supervisor verifies that any person required to operate a telehandler is trained and assessed competent in conduct of those operations. | |
| Operator/Maintainer reports damage to boom side windows on telehandlers or variable reach trucks as soon as it occurs? | | | | Operator reports damage to boom side windows on telehandlers or variable reach trucks as soon as it occurs and stop the job until the window is replaced. | |
| Operator/Maintainer of telehandlers warned of the dangers of operating their machines with the side screen broken or missing? | | | | Operators of telehandlers warned of the dangers of operating their machines with the side screen broken or missing. Side window on the boom side fitted with signage indicating machine guard. | |

| Prompt | Establis | Improvem | A/A | Explanation | Comments |
|-------------------------------------------------------------------------------------------------------------------------------|----------|----------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| Operator/Maintainer checks side window on the boom side fitted with signage indicating machine guard? | | | | Operator checks side window on the boom side fitted with signage indicating machine guard? | |
| Operator/Maintainer keeps completely within the telehandler cabin when operating the machine to keep away from the boom path. | | | | Operator keeps completely within the telehandler cabin when operating the machine to keep away from the boom path. Do not lean out of the side windows while operating. | |
| Operator/Maintainer stops work if personnel enter exclusion zone under suspended load or raised boom? | | | | Operator stops work if personnel enter exclusion zone under suspended load or raised boom. | |
| Operator/Maintainer operates telehandler within technical capabilities and limitations of the machine? | | | | Operator operates telehandler within technical capabilities and limitations of the machine. Do not operate equipment if not trained | |